



DET 20

Digital Earth Tester

DET 20 is a conventional type 3 digit LCD display which is designed to measure Earth Resistance, Soil Resistivity & Earth Voltage. It has a unique RSR technology in which even at the drop of battery voltage the measurement reading remain constant. DET 20 has 128Hz test frequency which eliminates the harmonics interference and has rechargeable long-life battery which reduces the cost of battery. Earth resistance is measured by three wires & Soil Resistivity is measured by four wire measurement techniques. This meter is shock proof, drop and dust proof. It has ABS casing which is useful for heavy duty. DET 20 is designed as per IS 9223.

Features

- ✓ 3 ½ digit LCD Display with max reading 1999.
- ✓ 3 terminal and 4 terminal Measurement Method
- ✓ Earth Resistance Range 0.01Ω to 1999Ω
- ✓ 4 Soil Resistivity Measurement
- ✓ Rechargeable Internal Ni-MH Battery
- ✓ Earth Measurement Voltage up to 200V
- ✓ Ratio Metric Synchronous Rectification



Applications

The integrity of the grounding system is very important in an electrical power system for the following reasons:

To maintain a reference point of potential (ground) for equipment and personnel safety. To provide a discharge point for travelling waves due to lightning. To prevent excessive high voltage due to induced voltages on the power system

Therefore to maintain sufficiently low resistance values of grounding systems, their periodic testing is required. The testing involves measurement to ensure that they do not exceed design limits.

The measurement of ground resistances may only be accomplished with specially designed test equipment. The most common method for measuring ground resistance uses the fall-of-potential principle of alternating current (AC) at higher frequency circulating between an auxiliary electrode and the ground electrode under test; the reading will be given in ohms and represents the resistance of the ground electrode to the surrounding earth.

Soil Resistivity is also the key factor that determines what the resistance of a grounding electrode will be, and to what depth it must be driven to obtain low ground resistance. The resistivity of the soil varies widely throughout the world and changes seasonally. Soil Resistivity is determined largely by its content of electrolytes, consisting of moisture, minerals, and dissolved salts. A dry soil has high resistivity if it contains no soluble salts. It figures has a direct impact on the overall sub-station resistance and how much earth electrode is required to achieve the desired values. Lower the resistivity, fewer the electrodes required to achieve the desired earth resistance value. Hence the Soil Resistivity is also important test.

The methods of measuring and testing the Earth Resistance and Soil Resistivity:

- 3 pole method used for Earth Resistance testing
- 4 pole method used for Soil Resistivity testing.

Technical Details

DET 20

Voltage withstand

In the event of a system fault, the instrument will withstand 240V AC, applied between any two terminals.

Dimensions

180mm(L) x 100mm(W) x 54mm(H)

Weight

800gms with battery charger.
5 KG with Kit

Accessories

Standard

- Earthing spike with screw Nut & Washer - 4 Nos.
- Wire Spool - (10,20,30,40 Mtrs) - 1 Set.
- Claw Hammer with Tubular Handle - 1 No.
- Carrying Bag - 1 No.
- Battery Charger - 1 No.
- Instruction Manual - 1 NO.

Typically used for

Standard

- Substation Earth Testing.
- To test telecom tower grounding, Railways Earthing.
- To test the quality of grounding without disconnecting the ground rod under test.
- Earth Resistance of Grid.



Earth Resistance Ranges

0.01Ω to 20.00Ω

0.1Ω to 200.0Ω

1Ω to 2000Ω

Accuracy (25°C ±5°C)

±1.5% of reading ±5 digits valid from 10% of reading to 95% of range.

Earth Voltage Range : 0-200V AC

Earth Voltage accuracy : 2% of Range

Earth Voltage resolution : 0.1V

Maximum Output Voltage Less than 40Vrms

Test Frequency 128Hz ± 10%

Test Current

20 Ω Range : 10mA AC RMS

200 Ω Range : 1mA AC RMS

2000 Ω Range : 100mA AC RMS

Test Current is generally constant throughout the range

Power Supply Internal, rechargeable Ni-MH 1.2V, 600mAh x 8nos.

Charging Time Recommended 16hrs.

Single Charge Battery life Approximately 5-6hrs of continuous operation on mid-range.

Interference

Interference voltage of 20V ±5% peak to peak, 50Hz in the potential circuit will have a maximum effect ±1% on the reading obtained from 20 Ω to 2KΩ ranges.

Influence of Temperature

±0.2% per °C over the temperature range 0-20°C and 28-55°C.

Temperature Range

Operating : 0°C to +55°C <90% RH

Storage : -20°C to +70°C <90% RH

Humidity

Operating : 95% RH non condensing max at 40°C

Storage : 93% RH non condensing max at 55°C

Flash Test : 2kV AC

ORDERING INFORMATION

Product

Order Code

DET-20

109393110

with Standard Accessories