

Electrical Test & Measurement Instruments





Features

- ✓ Contact / Non-contact type Detectors.
- ✓ Type tested at CPRI/ERDA
- ✓ Available in FRP Telescopic Rod.
- ✓ Colour Code models for different voltage levels.
- ✓ Indicates presence of High Voltage by Audio
- ✓ Annunciations as well as Visual Indications.
- ✓ Bright high intensity red LED's provide clear visual Bullet even in unfavourable daylight conditions.
- ✓ A Buzzer produces a loud beep which is audible even in noisy backgrounds.
- ✓ Supplied as a complete kit with HV Detector, Telescopic Fibre Glass Insulation stick and ergonomically designed sturdy carry bag.
- ✓ Self test button to test battery and proper functioning of HV detector.
- ✓ Powered by a single 9V battery type (6F22), easily replaceable on field.

HV 50, 132, 220 & 440 kV

High Voltage Detector


The Motwane HV Detector series provide an exceptional combination of user comfort and safety in one electrical safety device. The optimum LED layout, integrated audible signals and innovative self-test features form the basic elements on all voltage detection equipment types. HV Detector series are designed in contact type and non-contact type. The HV detectors are used to check for the absence or presence of voltage on medium and high voltage switchgear, transformers or overhead lines – electrical safety is imperative in all areas of power transmission and distribution at all voltage levels including MV, HV and EHV up to 440kV. It is available in FRP Telescopic Rod/FRP sectional hot stick. Powered by a single 9V battery. The HV detector starts annunciation with flashing red LED's and buzzer beeps indicating that the line is live and not safe to earth before carry any operations. HV Detector series is easy to use, hence jobs get done more quickly and safely. Reliably detecting high voltage on distribution and transmission voltage power lines is critical jobs performed by electric utility linemen.




Applications

Useful for Utility, Industrial, Railway and for Mine Safety applications like following.

- Non-contact detection of live voltages.
- Check and detect live high voltage cables.
- Trace live wires
- Detect residual or induced voltages.



Non Contact Type Probe.



Technical Details

High Voltage Detector

Technical Specification

Model	HV-50	HV-50P	HV-132	HV-132	HV-220	HV-440
Voltage Range	3kV - 50kV	240V - 36kV	11kV - 132kV	66kV - 132kV	33kV - 220kV	66kV - 440kV
Type	Non Contact	Non Contact	Non Contact	Contact	Non Contact	Non Contact
Sensing Distance	1mtr - 3mtr - 5mtr	1mtr - 3mtr - 5mtr	1mtr - 3mtr - 5mtr	1mtr - 3mtr - 5mtr	1mtr - 3mtr - 5mtr	1mtr - 3mtr - 5mtr

Power Specifications

Current Consumption	30mA maximum
Battery Low	7.2 V Nominal
Battery	9V / Battery type 6F22 or equivalent
Visual Indication	High Bright Red LED's flashing
Audible Indication	Buzzer beeps Loudly

Electrical Specifications

Insulation Resistance	Greater than 100MΩ at 1000V DC of HV Detector
Dielectric Strength	220KV AC, 50Hz of complete assembly

Environmental Specifications

Operating Temperature	5°C to 50°C
Humidity	<85% RH non-condensing
Storage Temperature	10°C to 60°C
	<85% RH non-condensing

Universal Link

Material	Glass Filled Nylon
Length	95mm Approx

Insulated Stick

Material	Fibre Glass (Sturdy & Rugged)
Length	Telescopic Extendable length.

Physical Specifications

Length	250mm Approx.
Diameter	108mm Approx
Weight	510 gm Approx

Accessories Standard

■ High voltage detector	: 01 No.
■ Universal Link	: 01 No.
■ Instruction Manual	: 01 No.
■ Rod Assembly	: 01 No.
■ Test & Calibration Certificate	: 01 No.

Accessories optional

■ Telescopic Rod Assy With Carrying Case, 1.23mtr	
■ Telescopic Rod Assy With Carrying Case 3mtr Long	
■ Telescopic Rod Assy WITH Carrying Case 5.5Mtr	
■ Hot Stick with Carrying case length 4 meter	
** Note: Accessories (Any one rod with device as per customer requirement)	

ORDERING INFORMATION

Product	Order Code
HV-50	109130010
HV-50P	109135010
HV-132	109131010
HV-132 - Contact	109142010
HV-220	109132010
HV-440	109133010
with Standard Accessories	

Notes : **1.** The Instrument is accompanied with Test & Calibration sheet. **2.** Test Facilities can be provided at the factory with the available test set-ups only. **3.** The company's policy includes continuous improvement of its product. We, therefore, reserve the right of any deviation from illustration or specifications without notice. **4.** Stated accuracies are valid from 10% of the range to 95% of the range. **5.** Accuracy specified for temperature range of 25°C ± 5°C & 55% RH ± 10%.

Contact Details

THE MOTWANE MANUFACTURING CO. PVT. LTD.

**Regd. Office & Factory :**

Gyan Baug Nashik Road, Nashik, 422101 Maharashtra, India

**Pune Unit :**

Unit No. 07 & 08, Electronic Sadan No. 2, MIDC, Bhosari, Pune - 411 026



www.motwane.com



Nashik Head Office : 91-0253 -2463752 / 53

Pune Office : 91-20-27122936, 27123176



<https://www.linkedin.com/company/motwanemanufacturing>

Scan the QR code to visit
Motwane's website

