

Electrical Test & Measurement Instruments





LR2045-S

Micro Ohm Meter

CAT III	IP	CE	USB	Bluetooth
600V	51			

The Motwane LR 2045-S capable of measuring low resistance with 1 micro-ohm resolution. It employs the proven 4-wire (4W) measurement where fixed DC current is supplied to DUT and voltage drop across the DUT is measured and displayed as proportional resistance reading. The meter is able to deliver guaranteed stable readings on inductive as well as resistive loads.

Features

- ✓ Back-EMF Protection
- ✓ Best Measurement **Accuracy of $\pm 0.05\% \pm 5 \text{ dgt}$**
- ✓ **Resolution $0.1 \mu\Omega$ on $2\text{m}\Omega$ range**
- ✓ Inbuilt Thermal Paper Printer
- ✓ Temperature Measurement & Temperature Correction Feature.
- ✓ 4.3" Colour TFT Digit Large And Clear Display
- ✓ Accurate & Stable Readings
- ✓ PC Interfacing With Software
- ✓ 4 Wire Measurement Method
- ✓ Sealed Soft Touch Membrane Keypad
- ✓ Pass/Fail Limit
- ✓ Bluetooth Interface And Cloud Connectivity Through MOT-WARE App

Applications

The equipment is used for quality checks, routine inspections, quick maintenance work across various industrial applications, and is suitable for design verification, testing, maintenance, QC/QA activities, as well as production use.

- Cables (cross-section below 200 sq mm)
- Transformers (up to 10MVA, dry type)
- Motors (up to 150HP or 110kVA)
- Generator (10kVA to 50kVA)
- Relays
- PC Boards
- Bus Bars
- Contactors
- Weld joints
- Electrodes
- Electronic components (circuit breakers, fuses, shunts, resistive parts, conductive elements, etc)

Technical Details

LR2045-S

Technical Specification

Display	4.3" Color TFT with backlit
Temperature correction	Range 0 to 100 deg, Accuracy + 1 deg, Resolution 0.1deg.
Temperature Channel	1
Printer	Built in Thermal Printer
PC Interface	USB
Report Storage	1000 Reports

Indications

- 4.3" Color TFT with backlit or range and $\Omega/m\Omega$ indications.
- LED indication for operation and pulse mode.
- Over range indication: Blinking zero display.
- Under Range Indication: All Display shows zero. (Not blinking)

Technical Specifications :

Range	Resolution	MAX CURRENT	ACCURACY $\pm (\%RDG + DIGITS)$
2m Ω	0.1 $\mu\Omega$	1 A	$\pm 0.5\%$ of reading ± 5 digits
20m Ω	1 $\mu\Omega$	1 A	$\pm 0.05\%$ of reading ± 5 digits
200m Ω	10 $\mu\Omega$	1 A	$\pm 0.05\%$ of reading ± 5 digits
2000m Ω	100 $\mu\Omega$	100mA	$\pm 0.05\%$ of reading ± 5 digits
20 Ω	1m Ω	10mA	$\pm 0.05\%$ of reading ± 5 digits
200 Ω	10m Ω	1mA	$\pm 0.05\%$ of reading ± 5 digits
2000 Ω	100m Ω	100uA	$\pm 0.05\%$ of reading ± 5 digits

Note : Accuracies are valid from 1/10th of the range to FS of range & valid

Temperature	25°C $\pm$ 3°C at 55% $\pm$ 10%RH.
Temperature Coefficient	100ppm/°C.
Open Circuit Voltage	15Volt $\pm$ 3volt.
Power Supply	Mains Input Voltage 115/230V AC $\pm$ 10%, 50/60Hz

Environmental Specifications:

Operating Temperature	0°C-55°C.
Storage Temperature	-10°C to 60°C.
Relative Humidity	95 % RH at 40°C max. (Non Condensing)

Safety

Measurement Category: CAT II (1000V)/CAT III (600V)
Reinforced insulation, IP 51
Relevant Standard Specifications: Safety According to
EN 61010-1, EMC According to EN 61326-1

Protection

Protection against EMF : 12kV-(1.2/50 μ s pulse).
Instrument Protected against mains overload
(Fuse 250mA)
All ranges are fuse protected. (Input fuse 1A).

Physical Specifications:

Dimensions : 368 mm (L) X 283 mm (W) X 188 mm (H)
Net Weight : 6.0kg (Approx)

Accessories

Standard

■ Test Lead Set 2 Meter	: 1 Set.
■ Mains Power Cord	: 1 No.
■ Fuse - 500mA 250V Slow Blow	: 1 No.
■ Fuse - 1.5A 250V Quick Blow	: 1 No.
■ Thermal Paper roll	: 1 No.
■ Instruction Manual	: 1 No.
■ Calibration Certificate	: 1 No.
■ USB Cable	: 1 No.
■ Temperature Measurement Probe	: 1 No.
■ Pen Drive with Software	: 1 No.

Note :

- Bluetooth Software (Optional)
- MOT-WARE Desktop Application (Optional)

ORDERING INFORMATION

Product	Order Code
LR2045-S with Standard Accessories	109290010

Contact Details

THE MOTWANE MANUFACTURING CO. PVT. LTD.

**Regd. Office & Factory :**

Gyan Baug Nashik Road, Nashik, 422101 Maharashtra, India

**Pune Unit :**

Unit No. 07 & 08, Electronic Sadan No. 2, MIDC, Bhosari, Pune - 411 026



www.motwane.com



Nashik Head Office : 91-0253 -2463752 / 53

Pune Office : 91-20-27122936, 27123176



<https://www.linkedin.com/company/motwanemanufacturing>

Scan the QR code to visit
Motwane's website

